WHAT IS CLAIMED IS:

- 1. A turbine bucket including a bucket airfoil having an airfoil shape, said airfoil having a nominal profile substantially in accordance with Cartesian coordinate values of X, Y and Z set forth in Table I wherein the Z values are non-dimensional values from 0.03 span to 0.95 span convertible to Z distances in inches by multiplying the Z values by a height of the airfoil in inches, and wherein X and Y are distances in inches which, when connected by smooth continuing arcs, define airfoil profile sections at each distance Z, the profile sections at the Z distances being joined smoothly with one another to form the bucket airfoil shape.
- 2. A turbine bucket according to Claim 1 forming part of a third stage of a turbine.
- 3. A turbine bucket according to Claim 1 wherein said airfoil shape lies in an envelope within ±0.150 inches in a direction normal to any airfoil surface location.
- 4. A turbine bucket according to Claim 1 including a platform, the height of the turbine airfoil from a root at a midpoint of the platform to a tip of the airfoil being 15.566 inches.
- 5. A turbine bucket including a bucket airfoil having an uncoated nominal airfoil profile substantially in accordance with Cartesian coordinate values of X, Y and Z set forth in Table I wherein the Z values are non-dimensional values from 0.03 span to 0.95 span

convertible to Z distances in inches by multiplying the Z values by a height of the airfoil in inches, and wherein X and Y are distances in inches which, when connected by smooth continuing arcs, define airfoil profile sections at each Z distance, the profile sections at the Z distances being joined smoothly with one another to form the bucket airfoil shape, the X and Y distances being scalable as a function of the same constant or number to provide a scaled-up or scaled-down airfoil.

- 6. A turbine bucket according to Claim 5 wherein the Z distances, when converted to inches, are scalable as a function of said same constant or number.
- 7. A turbine bucket according to Claim 5 forming part of a third stage of a turbine.
- 8. A turbine bucket according to Claim 5 wherein said airfoil shape lies in an envelope within ±0.150 inches in a direction normal to any airfoil surface location.
- 9. A turbine bucket according to Claim 5 including a platform, the height of the turbine airfoil from a root at a midpoint of the platform to a tip of the airfoil being 15.566 inches.
- 10. A turbine comprising a turbine wheel having a plurality of buckets, each of said buckets including an airfoil having an airfoil shape, said airfoil having a nominal profile substantially in accordance with Cartesian coordinate values of X, Y and Z set forth in Table I wherein the Z values are non-dimensional values

- from 0.03 span to 0.95 span convertible to Z distances in inches by multiplying the Z values by a height of the airfoil in inches, and wherein X and Y are distances in inches which, when connected by smooth continuing arcs, define the airfoil profile sections at each distance Z, the profile sections at the Z distances being joined smoothly with one another to form the bucket airfoil shape.
- 11. A turbine according to Claim 10 wherein the turbine wheel comprises a third stage of the turbine.
- 12. A turbine according to Claim 10 wherein the turbine wheel mounts 92 buckets and X represents a distance parallel to the turbine axis of rotation.
- 13. A turbine according to Claim 10 including a platform, the height of the turbine airfoil from a root at a midpoint of the platform to a tip of the airfoil being 15.566 inches.
- 14. A turbine according to Claim 10 including a platform for said buckets, the radial height between an axial centerline of said turbine wheel and a root of each airfoil at a midpoint of the platform thereof being 29.365 inches.
- 15. A turbine according to Claim 14 wherein the height of the turbine airfoil from the root at the midpoint of the platform to a tip of the airfoil being 15.566 inches.

- A turbine comprising a turbine wheel having a 16. plurality of buckets, each of said buckets including an airfoil having an uncoated nominal airfoil profile substantially in accordance with Cartesian coordinate values of X, Y and Z set forth in Table I wherein the Z values are non-dimensional values from 0.03 span to 0.95 span convertible to Z distances in inches by multiplying the Z values by a height of the airfoil in inches, and wherein X and Y are distances in inches which, when connected by smooth continuing arcs, define airfoil profile sections at each distance Z, the profile sections at the Z distances being joined smoothly with one another to form the bucket airfoil shape, the X and Y distances, coordinate non-dimensional Z values when the and converted to distances, being scalable as a function of the same constant or number to provide a scaled-up or scaled-down bucket airfoil.
- 17. A turbine according to Claim 16 wherein the turbine wheel comprises a third stage of the turbine.
- 18. A turbine according to Claim 16 wherein the turbine wheel mounts 92 buckets and X represents a distance parallel to the turbine axis of rotation.
- 19. A turbine according to Claim 16 including platforms for each of said buckets, the height of the turbine airfoil from a root at a midpoint of the platform to a tip of the airfoil being 15.566 inches.
- 20. A turbine according to Claim 16 including platforms for each of said buckets, the radial height between an axial centerline of said turbine wheel and a

root of each bucket at a midpoint of the platform thereof being 29.365 inches.

- 21. A turbine according to Claim 20 wherein the height of the turbine airfoil from the root at the midpoint of the platform to a tip of the airfoil being 15.566 inches.
- 22. A turbine according to Claim 16 wherein said airfoil shape lies in an envelope within ± 0.150 inches in a direction normal to any airfoil surface location.